

QCM-200AS2 Series Product Comparison Sheet

Name Function / Spec.	QCM-200AS2CS	QCM-200AS2RS	QCM-200AS2PS	QCM-200AS2MS
Voltage Supply	DC 12-30V / 0.6A	DC 12-30V / 0.6A	DC 12-30V / 0.6A	DC 12-30V / 0.6A
Optics coupling component	Yes	Yes	Yes	Yes
Watch Dog function	Yes	Yes	Yes	Yes
TVS Function	Yes	Yes	Yes	Yes
Date/Time Display	-	-	-	Yes
Communication Interface	CAN Bus	RS-485	Parallel (Binary / Gray / 7 Segment)	RS-485
Download Communication Port	RS-232			
QCM-Series Software Tool	QCM-200AS2 Lift LCD Editor			
PCB dimension	124x55	124x55	124x55	124x55
LCD dimension	72x40	72x40	72x40	72x40
LCD dpi	128x64 dots	128x64 dots	128x64 dots	128x64 dots
LCD Dots size	0.52 mm	0.52 mm	0.52 mm	0.52 mm
LCD color display	White words, icons w/ blue bkgnd. / black bkgnd.			
Special Settings ↓	Special settings are needed to be edit via QCM-200AS2 Lift LCD software. ↓			
Customer logo	-	-	-	Yes
LCD BL Power saving	0~600 Sec.	0~600 Sec.	-	-
Node Address	0~63 address	-	-	-
ID Code (4 bytes) for personalization	4 bytes	-	-	-
Enable Date and Time function	-	-	-	Yes
Message position	Up, Middle, Down	Up, Middle, Down	Up, Middle, Down	Up, Middle, Down